

## 7 | TECHNICAL DATA

Model	Capacity (racks / h)	Rinse System	Water consumption *		Total connected load (kW)			Total length  (in mm without drying zone)
			(l / h)	(l / rack)	with hot water supply (min. 50°C)	with cold water supply (min. 10°C) and heat recovery system C20	with cold water supply (min. 10°C)	
CN-A	100/170/220	Triple	230	1.05	28.50	28.50	37.50	1,800
CNE-A	110/180/240	Triple	170	0.71	25.70	25.70	31.70	2,300
CN-L-A	120/200/280	Triple	180	0.64	27.00	27.00	33.00	2,450
CN-S-A	150/240/340	Triple	180	0.53	27.65	27.65	33.65	2,700
CNE-S-A	180/250/350	Triple	180	0.51	27.90	27.90	33.90	3,200
CN-L-AA	190/260/360	Triple	210	0.58	35.20	38.20	44.20	3,450
CN-S-AA	200/270/390	Triple	210	0.54	35.85	38.85	44.85	3,600
CNE-S-AA	210/300/450	Triple	220	0.49	36.10	42.10	45.10	4,100

**Note:** 1) Add 4.9 kW and 400 mm when Dryer (DS) is ordered to all models.

- 2) PROTRONIC control is standard to all models. SMARTRONIC control is option for CN-A, CNE-A, CNL-A, CNS-A when space is limited, length reduce by 450 mm.  
3) Steam option is available to all models. Please contact HOBART office for more details.

\* Under optimized conditions